



Air & Vessel Traffic Management Systems

VETWEET VEHICLE MANAGEMENT SYSTEM

VetWEET is a vehicle management system, designed specifically for the movement of vehicles within the Airport Movement Area. It consists of a 1090MHz transmitter transponder with an embedded DGPS/SBAS module, which can be quickly and easily installed to an existing vehicle.

VetWEET improves situation awareness by providing identification and positioning information of equipped vehicles to a Controller based in the Control Tower. This is done via a Multilateration system and/or ADS-B ground stations installed in the airport. In order to ensure continuity of the service in the absence of GPS, the system also incorporates internal gyroscopes and an odometer.

DUAL-LINK CAPABILITY

Both versions are available with a dual-link capability by adding a HyperLan 5GHz or WiFi 2.4GHz module. This dual-link capability makes VetWEET the best solution for satisfying the Air Traffic Services and Fleet Management requirements of the modern airport.

VETWEET PLUS

VetWEET plus is an enhanced version of the standard system. It consists of a 1090MHz transceiver (Rx/Tx) and a 10.4 inch touch-screen display with an integrated on-board computer, installed within the vehicle.

This enhanced version allows vehicle drivers to navigate the Airport Movement Area, even in low visibility conditions, by means of a moving map onto which other vehicle and aircraft positions can be displayed.

VetWEET plus supports the digital communication of information between a vehicle drivers and the ATC Controllers/ Airport Operators.



SYSTEM ARCHITECTURE

The Tx/Rx transceiver component of VeTWEET has been designed for outdoor use in all weather conditions. It is easily installed on top of the vehicle by means of integrated magnets. The antenna (1090MHz, GPS, HyperLan or WiFi) and transceiver are housed within a radome and powered via RS422 through a car power socket.

The touch-screen on-board computer comprises an integrated central unit and a graphical 10.4 inch touch-screen display.

Main feature include:

- DGPS/SBAS position information
- ADS-B in/out
- TIS-B/FIS-B
- On board situational awareness
- Recognition capability
- Short and extended squitter transmission
- Ease of installation
- Cost and ease of maintenance
- Compact dimensions
- Easy to configure
- Low power consumption
- Low electromagnetic emission.

TECHNICAL FEATURES

Applicable Standards	CAO Annex 10, Vol.4
	RTCA DO-260A
	EEE 802.11/a-b-g

1090MHz antenna

Rx	
Bandwidth	ICAO compliant
Message types	DF17/18

Tx	
Bandwidth	ICAO compliant
Message types	DF11 (config. format) DF18 (config. format)
Transmitter frequency (jittered)	1Hz (DF11) 2Hz/0.2Hz (DF18 surface) 0.2Hz (DF18 identification) 0.2Hz (DF18 Oper. Status)
Output power:	40, 43 dBm (configurable)

Display

Type	TFT 800x600 pixel, 10.4"
Input devices	Resistive touch-screen
Backlight	Fluorescent backlight
Audio	Acoustic alarm

2.4GHz/5GHz antenna

Bit rate	up to 54Mbit/s
Operating frequency	2.4 - 2.5GHz 5.47 - 5.725GHz

Output power

2.4 - 2.5GHz	20 dBm EIRP (adjustable)
5.47 - 5.725GHz	30 dBm EIRP (adjustable)
Data encryption	WPA, WPA2, WEP

Environmental

Operating environment	
Temperature	-30 °C to +55 °C
Humidity	IP-67 compliant

Electrical

Input voltage	10.8 - 27V
Power consumption	< 10W

Interfaces

RS422 or Ethernet 10/100 BaseT (IEEE 802.3)



For more information please email infomarketing@selex-es.com

Selex ES S.p.A. - A Finmeccanica Company

Via Tiburtina, Km 12.400 - 00131 Rome - Italy - Tel: +39 06 41501 - Fax: +39 06 413133

This publication is issued to provide outline information only and is supplied without liability for errors or omissions. No part of it may be reproduced or used unless authorised in writing.

We reserve the right to modify or revise all or part of this document without notice.

2015 © Copyright Selex ES S.p.A.

www.selex-es.com

SSD MM07962 3-15