

RUGGED AND RELIABLE

DISCOVER THE AW109 TREKKER EMS

The AW109 Trekker is the newest light twin engine helicopter, equipped with skid landing gear, developed to provide the perfect solution for EMS operations.

High productivity, excellent flying qualities, high controllability and manoeuvrability, robustness and high inherent safety characterise the helicopter.

A spacious interior ensures successful completion of any EMS mission with access to the whole patient body.

AgustaWestland AW109 TREKKER EMS





DISTINCTIVE FEATURES

- Rugged skid landing gear
- State-of-the-art glass cockpit
- High payload.

ADVANCED AVIONICS

State-of-the-art Genesys Aerosystems glass cockpit

- Ergonomic and low workload cockpit layout
- Two large format 6" x 8" EFIS displays providing Primary Flight Display (PFD) and Multi-Function Display (MFD) information
- Integrated 3D Synthetic Vision with Highway-In-The-Sky (HITS) navigation
- Integrated Helicopter Terrain Awareness Warning System (HTAWS) with worldwide terrain and obstacle database
- Fully capable moving map
- Dual VHF / AM, dual VOR, GPS, ESIS
- Global Positioning System (GPS) augmented by the Wide Area Augmentation System (WAAS)
- Mode S transponder with ADS-B Out capability
- Integrated TAS capability
- Co-pilot 6" x 8" Primary Flight Display available on request.

VERSATILITY

- Ability to convert from 1 patient to 2
- Ability to configure for highly intensive medical procedures: i.e. ECMO or NeoNatal.

VALUE FOR MONEY

- Best in class payload, speed and full body access allows for the EMS operators to successfully get to and treat the patient in a timely and effective manner.

STATE-OF-THE-ART SAFETY

- High resistance cocoon-type airframe
- Crash resistant fuel system, crew and passengers seats
- Powerful PW207C turbo-shaft engines with FADEC
- Enhanced situational awareness to maximise safety levels
- 3-axis autopilot coupled to the GPS.

EXTENSIVE OPERATIONAL CAPABILITY

- Extended operating envelope (weight / altitude / temperature).



EMS TOP PERFORMER

- Versatile, high volume cabin, with space for 4 medical attendants and a single stretcher or 2 attendants in dual stretcher configuration, with full body access
- Comprehensive range of mission equipment including: Liquid or Gas Oxygen, suction, external rescue hoist, cable cutter, searchlight
- Large sliding doors allow for swift, easy loading and unloading of personnel
- More than 140 knots cruise speed, providing rapid response



AW109 TREKKER CHARACTERISTICS

Weights

MTOW	3,175 kg	7,000 lb
------	----------	----------

Performance (ISA, S.L., MTOW)

Max cruise speed	274 km/h	148 kt
Hovering IGE	4,724 m	15,500 ft
Hovering OGE	3,048 m	10,000 ft
Service Ceiling (MCP)	4,846 m	15,900 ft
Max Range*	867 km	468 nm
Max Endurance*	4 h 38 min	

Powerplant

Engines	2 x Pratt&Whitney Canada PW207C	
Power Rating - AEO Take-Off	2 x 548 kW	2 x 735 shp

Fuel Capacity

3-cell fuel system	575 l	152 USgal
4-cell fuel system	669 l	177 USgal

Seating

Crew / Passengers	1 or 2 pilots with 7 or 6 passengers
	1 or 2 pilots with 1 stretcher and 3/4 medical attendants
	1 or 2 pilots with 2 stretchers and 2 medical attendants

* with 525 kg usable fuel - no reserve - @ 5,000 ft



Leonardo - Società per azioni
Registered Head Office:
Piazza Monte Grappa, 4 - 00195 Rome - Italy
Tel. +39 06 324731 - Fax +39 06 3208621
Leonardo Helicopters
Head Office:
Via Giovanni Agusta, 520 - 21017 Cascina Costa di Samarate - Italy
Tel. +39 0331 229111



© Leonardo - Società per azioni

This document contains information that is proprietary to Leonardo - Società per azioni and is supplied on the express condition that it may not be reproduced in whole or in part, or used for manufacture, or used for any purpose other than for which it is supplied.

leonardocompany.com